



YOUR MOBILE VOICE JUST GOT STRONGER

MOTOTRBOTDM4000 SERIES DIGITAL TWO-WAY MOBILE RADIOS

From the delivery driver crisscrossing the city to the sanitation crew clearing streets, MOTOTRBOTM can transform your enterprise and make employee interactions smarter and safer. Our best-in-class audio and exceptional data capabilities empower people like never before.

Versatile and powerful, MOTOTRBO combines the best of two-way radio functionality with the latest digital technology. DM4000 Series radios integrate voice and data seamlessly, offer enhanced features that are easy to use, and deliver operations-critical advantages like integrated Bluetooth® and Intelligent Audio.

The DM4000 Series can remaster your workplace and the way people collaborate to help you achieve even greater efficiency.

AUDIO BEYOND EXPECTATIONS

When it comes to exceptional audio clarity, the quality of digital can't be denied. With the DM4000 Series mobiles, you get digital quality plus unique features to help your employees hear and speak clearly, wherever they work.

With Intelligent Audio, the radio volume automatically adjusts to compensate for background noise so workers don't have to adjust their radio volume to avoid missing a call in loud situations or disturbing others when they move into quiet places. Increased background noise suppression filters out unwanted external clamour — from road traffic to the roar of engines.

Bluetooth® audio, built in to the radio, provides voice communication with exceptional clarity — giving your people the freedom to move without wires. Also, IMPRES™ audio accessories enhance noise suppression and improve voice intelligibility for smarter audio than they've ever experienced before.

INTEGRATED DATA SOLUTIONS

DM4000 Series radios are available with integrated GPS that enables location tracking of mobile work teams and text messaging between radios enables communication when voice isn't feasible. The large, full-colour display operates in day or night mode, for easy viewing of contact lists, text messages and work order tickets even in bright sunlight. Models are also available that feature integrated Bluetooth enabling the radio to wirelessly interface with Bluetooth-enabled devices such as barcode scanners and magnetic card readers to facilitate the collection of critical information in the field.

MOTOTRBO's Application Developer Program is the largest in the industry and offers customised data applications that allow you to adapt your radios to your business challenges. With a wide range of solutions available, data applications answer your objectives—from work order ticket management to telephony integration, and more.

HIGH-POWERED PERFORMANCE

Because MOTOTRBO uses TDMA digital technology, you get integrated voice and data, twice the calling capacity and clearer voice communications. Also, the smart IMPRES™ technology in our high-powered accessories enables easier communications — everywhere your people travel.

RICH FUNCTIONALITY

DM4000 Series radios offer plenty of features your business seeks — including enhanced call signalling, basic and enhanced privacy-scrambling, option board expandability, the Motorola-unique transmit interrupt suite to prioritise critical communication the moment you need it and compatibility with SCADA solutions for utility and public service monitoring and alarms. Programmable button features appear on the display for easy viewing and quick access. And when workers can't be distracted, customisable voice announcement provides audible confirmation of channel and zone changes as well as programmable button features, eliminating the need to view the display.

EXPANDED CAPACITY AND COVERAGE

Your work crews are on the go — picking up loads, dropping off cargo, repairing roads or restoring power after a storm. That's why you need the far-reaching performance of MOTOTRBO.

IP Site Connect helps to dramatically improve customer service and productivity by using the Internet to extend coverage to create a wide area network, enhance single site coverage or link geographically dispersed locations. Capacity Plus provides single-site trunking expanding capacity to over 1,000 users. Combining the benefits of both solutions, Linked Capacity Plus is an entry-level, multi-site trunking solution that expands capacity and extends coverage so large work teams can stay connected across a wide area. So whether you want expanded coverage at a single site or across multiple ones, MOTOTRBO can be scaled to your needs.

MIGRATE AT YOUR OWN PACE

Keeping operations running smoothly during a change in communication systems is vital to business. It's easy to migrate to digital with DM4000 Series radios because they operate in analogue and digital mode while the dynamic mixed mode repeater functionality streamlines automatic switching between analogue and digital calls. So you can begin using MOTOTRBO radios and repeaters on your existing analogue system, and when your time and budget allow, move to digital at your own pace.

DAY-IN, DAY-OUT DURABILITY

DM4000 Series mobile radios undergo Motorola's unique Accelerated Life Testing to help ensure they will stand up to the hard knocks of everyday use. For even greater peace of mind, they are backed by a two-year Standard Warranty.

BE READY FOR
THE FUTURE WITH THE
RIGHT STANDARD
MOTOTRBO complies with the
globally-recognised European
Telecommunications Standard
Institute (ETSI) Digital Mobile
Radio (DMR) Tier 2 standard
for professional two-way radio

DMR is widely supported by the leading two-way manufacturers in the industry and the most widely deployed digital mobile radio technology worldwide. This open standard assures long-term sustainability and creates a community of manufacturers who build interchangeable equipment that can compete on features, benefits and price.





DM4000 SERIES SPECIFICATIONS

GENERAL SPECIFICATIONS							
		DM4600	DM4600 / DM4601		DM4400 / DM4401		
		VHF	UHF Band 1	VHF	UHF Band 1		
Channel Capacity		Up to 1,000		32			
T: I DE Ott	Low Power	1-25 W	1-25 W	1-25 W	1-25 W		
Typical RF Output	High Power	25-45 W	25-40 W	25-45 W	25-40 W		
Dimensions (H x W x L)		53.3 x 175.3 x 205.7 mm (2.1 x 6.9 x 8.1 in)		53.3 x 175.3 x 205.7 mm (2.1 x 6.9 x 8.1 in)			
Weight		1.8 kg (3.9 lbs)		1.8 kg (3.9 lbs)			
Current Drain	Standby	0.81 A max	0.81 A max	0.81 A max	0.81 A max		
	Rx @ Rated Audio	2 A max	2 A max	2 A max	2 A max		
	Transmit	1-25 W: 11.0 A max 25-45 W: 14.5 A max	1-25 W: 11.0 A max 25-40 W: 14.5 A max	1-25 W: 11.0 A max 25-45 W: 14.5 A max	1-25 W: 11.0 A max 25-40 W: 14.5 A max		

RECEIVER: DM4000 SERI	ES			
	VHF	UHF Band 1		
Frequencies	136-174 MHz	403-470 MHz		
Channel Spacing	12.5 kHz / 20 kHz / 25 kHz			
Frequency Stability (-30°C, +60°C, +25°C Ref)	±	0.5 ppm		
Analogue Sensitivity (12dB SINAD)	0.3uV 0.22uV (typical)			
Digital Sensitivity	5% E	BER : 0.3uV		
Intermodulation (TIA603D)	78 dB	75 dB		
Adjacent Channel Selectivity (TIA603D)	50 dB @ 12.5 kHz 80 dB @ 25 kHz	50 dB @ 12.5 kHz 75 dB @ 25 kHz		
Spurious Rejection (TIA603D)	80 dB	75 dB		
Rated Audio	7.5 W (Ex	(Internal) ternal - 8 ohms) ternal - 4 ohms)		
Audio Distortion @ Rated Audio	3%	(typical)		
Hum and Noise	-40 dB @ 12.5 kHz/-45 dB @ 25 kHz			
Audio Response	TIA603D			
Conducted Spurious Emission (TIA603D)	-	57dBm		

	· · · · · · · · · · · · · · · · · · ·			
TRANSMITTER: DM4000 SERIES				
	VHF	UHF Band 1		
Frequencies	136-174 MHz	403-470 MHz		
Channel Spacing	12.5 kHz / 20 kHz / 25 kHz			
Frequency Stability (-30°C, +60°C, +25°C Ref)	± 0.5 ppm			
Low Power Output	1-25 W	1-25 W		
High Power Output	25-45 W	25-40 W		
Modulation Limiting	± 2.5 kHz @ 12.5 kHz/± 5.0 kHz @ 25 kHz			
FM Hum and Noise	-40 dB @ 12.5 kHz/-45 dB @ 25 kHz			
Conducted/Radiated Emission	-36 dBm < 1 GHz/-30 dBm > 1 GHz			
Adjacent Channel Power	60 dB @ 12.5 kH	lz/70 dB @ 25 kHz		
Audio Response	TIA	603D		
Audio Distortion	3	3%		
FM Modulation	12.5 kHz: 11K0F3	E / 25 kHz: 16K0F3E		
	12.5 kHz Data: 7k	(60F1D & 7K60FXD		
4FSK Digital Modulation	12.5 kHz Voice: 7	K60F1E & 7K60FXE		
	Combination of 12.5 kH	z Voice & Data: 7K60F1W		
Digital Vocoder Type	AME	BE+2™		
Digital Protocol	ETSLTS 102	2 361-1, -2, -3		

MILITARY STANDARDS: DM4000 SERIES										
	810C		810D		810E		810F		810G	
APPLICABLE MIL-STD	METHOD	PROCEDURES	METHOD	PROCEDURES	METHOD	PROCEDURES	METHOD	PROCEDURES	METHOD	PROCEDURES
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	1, 11	501.2	I/A1,II/A1	501.3	I/A1,II/A1	501.4	I/Hot, II/Hot	501.5	I/A1, II
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II
Temperature Shock	503.1	-	503.2	I/A1/C3	503.3	I/A1/C3	503.4	I	503.5	I/C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	1, 11	506.2	1, 11	506.3	1, 11	506.4	1, 111	506.5	1, 111
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.5	II - Aggravated
Salt fog	509.1	-	509.2	-	509.3	-	509.4	-	509.5	-
Dust	510.1	ı	510.2	ı	510.3	ı	510.4	ı	510.5	ı
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	1/24	514.6	1/24
Shock	516.2	1, 11	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.6	I, IV, V, VI

GPS: DM4401 / DM4601				
Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)				
< 1 minute				
< 10 seconds				
< 5 metres				

ENVIRONMENTAL SPEC DM4000 SERIES	CIFICATIONS:
Operating Temperature	-30° C / +60° C
Storage Temperature	-40° C / +85° C
Thermal Shock	Per MIL-STD
Humidity	Per MIL-STD
ESD	IEC 61000-4-2 Level 3
Dust and Water Intrusion	IP54, MIL-STD

Specifications subject to change without notice. All specifications shown are typical.

Radio meets applicable regulatory requirements.

BLUETOOTH: DM4401 / DM4601				
Version	Supports Bluetooth® 2.1 + EDR Specification			
Profiles Supported	Bluetooth Headset Profile (HSP), Serial Port Profile (SPP), Motorola fast push-to-talk.			
Devices Supported	Radio supports 1 Bluetooth audio accessory and 1 Bluetooth data device simultaneously			
Range	Class 2, 10 metres			

For more information on how to make sleek and stylish work for you, visit motorolasolutions.com/mototrbo or find your closest Motorola representative or authorised Partner at www.motorola.com/Business/XU-EN/Contact_Us

